



Product Service

# Compliance Document

No. D 041829 3250 Rev. 01

**Holder of Certificate:** **Huawei Technologies Co., Ltd.**  
Administration Building  
Headquarters of Huawei Technologies Co., Ltd.  
Bantian, Longgang District  
518129 Shenzhen  
PEOPLE'S REPUBLIC OF CHINA

**Product:** **Converter**  
**SOLAR INVERTER**

This Compliance document confirms the compliance with the listed standards on a voluntary basis. It refers only to the sample submitted for testing and certification and does not certify the quality or safety of the serial products. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 704091608614-01

**Date,** 2020-08-19

( Zhengdong Ma )

# Compliance Document

No. D 041829 3250 Rev. 01

**Model(s):** SUN2000-36KTL, SUN2000-33KTL-A

## Parameters:

d.c. Max. Input Voltage:	1100 Vd.c.
d.c. MPP Range:	200-1000 Vd.c.
d.c. Max. Input Current:	22 A /22 A /22 A /22 A
Isc PV:	30 A /30 A /30 A /30A
a.c. Output Nominal Voltage:	For model SUN2000-36KTL: 3/N/PE~ 400V 3~ 400V (optional) 3~ 480V (optional) For model SUN2000-33KTL-A: 3/N/PE~ 400V
a.c. Nominal Operating Frequency:	50 Hz
a.c. Output Max. Current:	For model SUN2000-36KTL: 57,8 A (@rated voltage 400V) 48,2 A (@rated voltage 480V) For model SUN2000-33KTL-A: 48 A
a.c. Output Rated Power:	36 kVA (SUN2000-36KTL) 30 kVA (SUN2000-33KTL-A)
a.c. Output Max. Power:	40 kVA (SUN2000-36KTL) 33 kVA (SUN2000-33KTL-A)
Power factor(adj.):	0,8(lagging)...0,8(leading)
Operating Temperature Range:	-25 °C...+60 °C
Protective Class:	I
Ingress Protection:	IP65

**Tested according to:** EN 50549-2:2019/AC:2019